PREX Dump configuration Ciprian Gal UVa

Radiation - entire run values

Total NEIL/cm2 uncert Ratio to	P1 uncert				
		Total NEIL/cm2	uncert	Ratio to P1	uncert
PREX1 (ERR dump) 4.60E+10 1.79E+09 1.00	0.06	7.43E+10	4.92E+09	1.00	0.09
PREX1 (actual dump) 4.05E+10 1.68E+09 0.88	3 0.05	7.78E+10	5.39E+09	1.05	0.10
PREX2 ERR 4.96E+09 6.72E+08 0.11	0.02	1.09E+10	2.61E+09	0.15	0.04
PREX2 current 5.77E+10 5.69E+09 1.25	5 0.13	7.60E+10	1.85E+10	1.02	0.26
P2 with P1pipe 2.12E+10 3.38E+09 0.46	6 0.08	4.39E+10	1.31E+10	0.59	0.18
P2 current+4in 4.46E+10 4.64E+09 0.97	7 0.11	6.68E+10	1.45E+10	0.90	0.20
P2 current+Conc 2.38E+10 3.44E+09 0.52	2 0.08	2.76E+10	1.04E+10	0.37	0.14
P2 current+ (Conc*2) 1.54E+10 1.81E+09 0.33	3 0.04	1.72E+10	4.07E+09	0.23	0.06
P2 current+ (Conc*0.5) 2.70E+10 2.63E+09 0.59	0.06	2.40E+10	6.13E+09	0.32	0.09
P2 current+Poly 2.19E+10 3.09E+09 0.48	3 0.07	5.40E+10	1.59E+10	0.73	0.22
P2 current+4in+1ftCont 1.83E+10 2.84E+09 0.40	0.06	2.69E+10	7.95E+09	0.36	0.11
P2 current + donut shield 5.27E+10 5.61E+09 1.15	5 0.13	8.28E+10	1.98E+10	1.11	0.28
CREX ERR 6.73E+09 2.05E+09 0.15	5 0.04	1.31E+10	6.57E+09	0.18	0.09
C5 current 3.86E+10 7.80E+09 0.84	4 0.17	4.70E+10	1.96E+10	0.63	0.27
C5 current+4in 9.86E+09 2.61E+09 0.21	1 0.06	3.80E+10	2.11E+10	0.51	0.29
C5 P1pipe 7.31E+10 1.12E+10 1.59	0.25	1.06E+11	3.38E+10	1.43	0.47
C5 current+Conc 2.23E+10 5.78E+09 0.49	9 0.13	3.21E+10	1.65E+10	0.43	0.22
C5 current+(Conc*2) 1.73E+10 3.23E+09 0.38	3 0.07	2.68E+10	1.00E+10	0.36	0.14
C5 current+(Conc*0.5) 1.70E+10 3.35E+09 0.37	7 0.07	1.09E+10	5.20E+09	0.15	0.07
C5 current+Poly 1.86E+10 5.13E+09 0.40	0.11	1.40E+10	1.01E+10	0.19	0.14
C5 current+ 2Pipe septum 3.85E+10 8.70E+09 0.84	4 0.19	9.65E+10	3.52E+10	1.30	0.48
C5 current+ 4in+1ftConc 1.01E+10 3.28E+09 0.22	2 0.07	3.85E+10	2.35E+10	0.52	0.32
C5 current+2Pipe+donut shield 4.09E+10 7.86E+09 0.89	9 0.17	4.73E+10	2.41E+10	0.64	0.33


Area for HRS det: 4e5 cm² Area for Under det: 6e4 cm²

Todo list

- More work is going to have to be done to optimize the shielding
- Sanghwa and I went over to the hall and we made some more measurement of the dimensions and locations of the electronics boxes on the HRS (fisheye picture and video at: <u>https://goo.gl/</u> <u>photos/Q2RjKWvZrBsajLcCA</u>)
 - More pictures on hallaweb: <u>http://hallaweb.jlab.org/parity/</u> <u>prex/beamline/hrsPlatform/</u>
- Maduka has sent us his geometry implementation: <u>http://galileo.phys.virginia.edu/~mmk6qa/Geant4_simulations/</u>
 - unfortunately they are coded in c++ source files but the information is very useful nonetheless


PREX2 - Under HRS detector

current setup + 1 ft Concrete




PREX2 - Under HRS detector

current setup + 1 ft Concrete



CREX - Under HRS detector


current setup + 1 ft Concrete




CREX - Under HRS detector











PREX2 - current dump























current setup


current setup + 0.5 ft concrete shield








current setup + 2 ft concrete shield














current setup + donut shield:


- * 131 cm in z
- * 20 cm in r (46 to 66 cm)
- * DS edge ~50 cm from the edge of the hall (would require some refinement to fit in)









current setup + donut shield



25







27

current setup


PREX1 dump setup




current setup



PREX1 dump setup





current setup + 1 ft concrete shield



current setup


current setup + 2 ft concrete shield (2x stat)






33

current setup + 0.5 ft concrete shield (2x stat)






current setup + 0.5 ft concrete shield


35

current setup + 1 ft Poly shield




current setup

current setup + 1 ft Poly shield





37

current setup + 2PipeSeptum




current setup + 2PipeSeptum







40




current setup + 2PipeSeptum+donut shield




current setup + 2PipeSeptum+donut shield




PREX 2 Dump configuration



- For PREX2/CREX we will not need to use the diffuser
- I have only implemented the beam pipe until the vacuum window and added the Al wall





PREX 1 dump configuration



- Dump configuration was different than what we had in the simulation
- The beam pipe has an Aluminum aperture that is about 4in in diameter in about the same location as the donut is now

GDML implementation






- Furthermore Kent noticed that the neck down in my configuration didn't match the drawing (or reality)
- now the neck-down is right after the wall similarly to what we have in the hall


Shielding concept






- Sanghwa, Dave and I went over to the hall and we made some measurement of the space available to us with the HRS parked in the 12.5 deg position
- I implemented 3 simple 1 foot thick shielding blocks in the simulation (ran for both concrete and Polyethylene)


Hall Configuration



10 cm thick Steel wall (in green) is not present in our simulation




Hall Configuration



- 10 cm thick Steel wall (in green) is not present in our simulation
- moreover, the hrs "electronics box" we have now doesn't cover the whole area where electronics exist and may be too forward


Hall Configuration




PREX2 - HRS rad damage

summary histogram per electron on target| neilLogX

summary histogram per electron on target| neilLogX



Black: current setup Red: current setup + 4 in donut Green: PREX 1 dump Blue: current setup + concrete Shield Magenta: current setup + Poly Shield



 Best configuration seems to be the PREX1 beam pipe, followed closely by the current pipe with shielding


CREX - HRS rad damage

summary histogram per electron on target| neilLogX

 10^{-3} N N Ò က S C C C **HRS side HRS unde** Hall det 10^{-4} 10^{-5} 10^{-6} 10⁻⁷ 1001 Tot 1001 Avg 1004 Tot 1004 Avg 1005 Tot 1005 Avg 1102 Tot 1102 Avg 2005 Tot 2005 Avg

summary histogram per electron on target |neilLogX


Black: current setup Red: current setup + 4 in donut Green: PREX 1 dump Blue: current setup + concrete Shield Magenta: current setup + Poly Shield




• For CREX having a large aperture can provide significant improvement

Plots with electrons plus gammas


PREX2 - current dump



current setup




current setup



56

current setup + 1 ft concrete shield


current setup





57


current setup + 1 ft Poly shield


current setup











current setup + 1 ft Poly shield

62